

## DS-2CE16C0T-IRPF



- HD 720p bullet camera
- Smart IR: up to 20 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

## ▪ Specification

Camera	
Image Sensor	1 MP CMOS
Max. Resolution	1296(H) × 732(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm and 6 mm fixed focal lens
Focal Length & FOV	70.9° (3.6 mm), 92° (2.8 mm), 56.7° (6 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 20 m
Image	
Frame Rate	720p @ 25 fps/720p @ 30 fps
SNR	>62dB
Noise Reduction	2D DNR
Interface	
Video Output	1 HD analog output
General	
Power	12 V DC ± 15%, max. 4 W
Dimension	Φ 70 mm × 154.5 mm ( 2.76" × 6.08")
Weight	Approx. 300 g (0.66 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Approval	
Protection	IP67

## ▪ Available Model

DS-2CE16COT-IRPF(2.8mm)

DS-2CE16COT-IRPF(3.6mm)

DS-2CE16COT-IRPF(6mm)

DS-2CE16COT-IRPF(2.8mm)(SEGO)

- **Accessory**

- **Optional**

**DS-1280ZJ-XS  
Junction Box**



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

