

DS-PHA64-Kit-WB AX Hybrid Pro Kit (433MHz)



- DS-PHA64-LP *1
- DS-PK1-LRT-HWB *1
- DS-PD1-MC-WS *1
- DS-PDP18-EG2 *2
- DS-PKF1-WB *1
- DS-PT-M1 *2

▪ Specification

Software features	
Zones	64 (8 On-board zones, max 8 wired PIRCAM)
Area	32
User	Installer: 1 Administrator: 1 Operator: 62
SMS notification	Support (with GPRS/3G/4G module)
Onboard video clips	4
ARC protocol	ISAPI: Supports iVMS-4200 client software and web client Cloud P2P: Supports cloud P2P privacy protocol DC-09: ARC accessible (ADM-CID/SIA-DCS) CSV-IP: Supports CSV-IP ISUP: Supports ISUP 5.0
Programming tools	Web/iVMS-4200/Hik-Partner Pro/Keypad
Firmware upgrade	Web/iVMS-4200/Hik-Partner Pro
End of Line Resistance	Support 1K, 2.2K, 4.7K, 5.6K, 6.8K, 8.2K
Hardware features	
Alarm input	64 (Including 8 on-board zones)
Alarm output	64 (Including 2 on-board relay outputs and 2 on-board I/O outputs)
Power Output	1. Bell: maximum 12V 1.2A 2. AUX: maximum 12V 1.5A
3/4G on board	Optional
GPRS on board	Optional
Wi-Fi	802.11b/g/n (2.4GHz)
Bus	1 Speed-X bus
Sounder output	1 Wired on-board sounder output
Tamper-Proof	1 switch to detect removal from mounting 1 switch to detect front cover open
Network interface	1 RJ45 10M/100M Ethernet interface
Electrical characteristics	
Power interface	100 to 240 VAC (on-board power transformer)
Power Consumption	1. 220V power supply ① With an alarm: 2A, 32W ② Without an alarm: 250mA, 4W 2. 13.5V battery supply ① With an alarm: 1.7A, 25W ② Without an alarm: 200mA, 2.7W
Battery type	Lead acid battery (12V 7Ah, battery is not included by default)
Battery life span	Up to 36hrs

Display	
Indicator	4 On-board LEDs: ① 1 AC power LED indicator (Green) ② 1 System status LED indicator (Green/Red) ③ 1 PSTN status LED indicator (Green/Red) ④ 1 Mobile communication status LED indicator (Green/Red)
General	
Operation temperature	-10°C to 40°C
Operation humidity	10% to 90%
Shell material	Plastic
Color	White
Dimension(WxHxD)	261 mm × 199 mm × 86.4 mm
Weight	997 g
Device management	
Tag	64
Keyfob	64
Keypad	8
Wireless sounder	16

▪ Available Model

DS-PHA64-Kit-WB

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

